



# Grabo Triumph

| Technical parameter                    | Standard       | Unit               | Result                                   |
|--|----------------|--------------------|--|
| <b>DESCRIPTION</b>                     |                |                    |  |
| Construction                           |                |                    | Non-directional homogeneous flooring     |
| Product specification (Binder content) | EN ISO 10581   |                    | Type I.                                  |
| Total thickness                        | EN ISO 24346   | mm                 | 2.0                                      |
| Width of roll                          | EN ISO 24341   | m                  | 2  |
| Length of roll                         | EN ISO 24341   | lm                 | 20                                       |
| Total weight                           | EN ISO 23997   | kg/m <sup>2</sup>  | 2.9                                      |
| <b>CLASSIFICATION</b>                  |                |                    |  |
| European classification                | ISO 10874      | class              | 34 / 43                                  |
| Residual indentation                   | EN ISO 24343-1 | max. mm            | 0.1                                      |
| Dimensional stability                  | EN ISO 23999   | max. %             | 0.2                                      |
|  | EN ISO 23999   | average %          | 0.1                                      |
| Curling                                | EN ISO 23999   | max. mm            | 8  |
| <b>PERFORMANCE</b>                     |                |                    |  |
| Abrasion group                         | MSZ EN 660-1   | class              | T  |
| Fire resistance                        | EN 13501-1     | class              | Bfl-s1                                   |
| Slip resistance                        | DIN 51130      |                    | R9                                       |
|  | EN 13893       |                    | DS                                       |
| Castor chair resistance                | ISO 4918       |                    | ✓  |
| Light fastness                         | EN ISO 105-B02 | grade              | 6  |
| Thermal resistance                     | EN 12524       | m <sup>2</sup> K/W | 0.012                                    |
| Electrical resistance                  | EN 1815        | kV                 | < 2 / Antistatic                         |
| Chemical resistance                    | EN ISO 26987   |                    | ✓  |
| Hygiene                                |                |                    | Bacterial resistant                      |
| Surface treatment                      |                |                    | iGUARD PUR Surface                       |
| Environmental attributes               |                |                    | Phthalate-, solvent and heavy metal free |
| Seaming method                         |                |                    | heat or cold weld                        |
| Content of PCP                         | EN 12673       |                    | Does not contain                         |
| Formaldehyde emission                  | ENV 717-1      |                    | E1 (no emission)                         |