

Product Definition

Konstruktion	High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content
Descripción	Hochleistungsfähige Luxus-Vinylfliese enthält 39 % recycelten Pre-Consumer Anteil
Description	Loseta LVT de alto rendimiento con 39% de contenido reciclado pre-consumo
Type	Le vinyle LVT haute performance contient 39% de contenu recyclé pré-consommation Hoogwaardige Luxe Vinyl Tegel bevat 39% pre-consumer gerecyclede content


Finish

Oberflächenbeschichtung	Ceramor™ - UV Stabilized Ceramic Bead Coating
Acabado	Ceramor™- UV-stabilisierte keramische Perldeckschicht
Finition	Ceramor™ tratamiento de superficie de cerámica resistente a UV
Slijtlaag	Ceramor™ - traitement de surface à base de céramique Ceramor™ - UV-gestabiliseerde keramische coating

Wear Layer Thickness / Nutzschildtdicke / Espesor de la capa de uso / Épaisseur couche d'usure / Dikte slijtlaag	0.55 mm (EN ISO 24340)
Total Weight / Gesamtgewicht / Peso Total / Poids total / Totaalgewicht	6880 g/m ² (EN ISO 23997)
Total Thickness / Gesamtdicke / Espesor Total / Épaisseur totale / Totale dikte	4.5 mm (EN ISO 24346)
Backing Type / Rückenkonstruktion / Soporte / Sous-couche / Ruguitvoering	Sound Choice™ Acoustic Backing
Wear Classification / Beanspruchungsklasse / Clasificación al tráfico / Classement d'usage et de confort / Gebruiksintensiteit	EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial

Radiant Panel / Schwerentflammbarkeit / Clasificación Al Fuego / Classement feu / De Radiant Panel Test	Euroclass Bfl s1 (EN 13501)
Dimensional Stability / Dimensionsstabilität / Estabilidad Dimensional / Stabilité dimensionnelle / Dimensionele stabiliteit	≤ 0.25 % (ISO 23999)
Curling / Wellung / Abarquillamiento / Incurvation / Opmrollen	≤ 2 mm (ISO 23999)
Flexibility / Flexibilität / Flexibilidad / Flexibilité / Flexibiliteit	Method A - Pass (EN ISO 24344)
Abrasion Resistance / Abriebshegung / Resistencia a la abrasión / Groupe d'abrasion / Slijtweerstand	Group T (EN 660-2)
Residual Indentation / Resteindrucksverhalten / Huella residual / Poinçonnement statique rémanent / Indrukbestendigheid	≤ 0.2 mm (EN ISO 24343-1)
Chemical Resistance / Chemische Beständigkeit / Resistencia a los productos químicos / Résistance aux produits chimiques / Chemische bestendigheid	(EN ISO 26987) Very Good
Impact Sound Insulation (ΔL_w) / Trittschallverbesserungsmaß / Aislamiento acústico al impacto / Réduction du bruit d'impact / Contactgeluid absorptie	16 dB (EN ISO 10140-3)
Determination of Anti-Slip / Rutschhemmung / Resistencia al deslizamiento / Glissance humide / Slipweerstand	R9, R10 (DIN 51130)
Pendulum Dry 4S	36+ Low slip potential (BS 7976-2)

Style A004 (Textured Woodgrains) A002 (Natural Woodgrains) 25 x 100 cm - 2.5m² Box (EN ISO 24342)



17

Interface European Manufacturing B.V.
Industrielaan 15
3925 BD
Scherpenzeel
The Netherlands

DOPPBRG – AHCK3R

EN 14041:2004
Notified Body - 0493

Resilient floor covering for internal use.
Classification Class 33/42 (EN ISO 10874)
Reaction to fire Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance Class DS (See EN 14041, clause 4.5)
Formaldehyde E1 (see EN 14041, clause 4.3)
Anti-static <2.0kV (See EN 14041, clause 4.6.1)

www.interface.com/lvt-emea



21


Interface European Manufacturing B.V.
Industrielaan 15
3925 BD
Scherpenzeel
The Netherlands

DOPPBRG – AHCK3R


EN 14041:2004
Approved Body - 0321

Resilient floor covering for internal use.
Classification Class 33/42 (EN ISO 10874)
Reaction to fire Class Bfl-s1 (see EN 14041, clause 4.1)
Slip resistance Class DS (See EN 14041, clause 4.5)
Formaldehyde E1 (see EN 14041, clause 4.3)
Anti-static <2.0kV (See EN 14041, clause 4.6.1)


www.interface.com/lvt-emea




HERRINGBONE




ASHLAR




31




42




NCS
Bfl-s1 L




≥0.30




≤2.0 kV




16dB




≥7




1




2



3




4



5

EMISSIONS DANS L'AIR INTÉRIEUR



Compliant with:
• AgBB
• LEED EQ
4.3 credit