



Technical Specifications

Product Definition	Microtuft Patterned Level Loop Pile						
Konstruktion	Gemusterte Microtuft-Schlingenqualität						
Descripción	Moqueta modular bucle de bajo perfil con diseño (Microtuft)						
Description	Dalle de moquette Microtuft à velours bouclé						
Type	Microtuft bouclé						
Descrizione	Bouclé microtuft						
Pile Material	100% Recycled Solution Dyed Nylon						
Polfasermaterial	100% recyceltes Polyamid garngefärbt						
Composición Fibra	100% Poliamida reciclada tintada en masa						
Composition	100% Polyamide recyclé teint masse						
Poolmateriaal	100% Solution Dyed Gerecycled Polyamide						
Fibra	100% Poliamide tinta in massa riciclata						
Pile Yarn Weight / Poleinsatzgewicht / Peso Fibra / Poids de fibre / Poolinzetgewicht / Peso Felpa	360 g/m ² ± 5%						
Total Weight / Gesamtgewicht / Peso Total / Poids total / Totaalgewicht / Peso Totale	3614 g/m ² ± 5%						
Total Thickness / Gesamtdicke / Espesor Total / Epaisseur totale / Totale dikte / Altezza Totale	4,4 mm ± 0,5 mm						
Gauge/Ends 10 cm / Teilung x 10 cm / Galga x 10 cm / Jauge-Rangs par 10 cm / Rijen per 10 cm / Serraggio x 10 cm / Tufts per m ² / Noppenzahl/m ² / Puntadas m ² / Densité du tuft par m ² / Aantal noppen per m ² / Densità Punti	5/64 – 50.4						
Backing Type / Rückenkonstruktion / Soporte / Sous-couche / Rugitvoering / Sottofondo	CQuest™Bio						
Wear Classification / Beanspruchungsklasse / Clasificación al tráfico / Classement d'usage et de confort / Gebruiksintensiteit / Resistenza all'usura	Heavy Contract (EN 1307) Class 33 / LC1						
Radiant Panel / Schwerentflammbarkeit / Clasificación Al Fuego / Classement feu / De Radiant Panel Test / Valutazione delle proprietà ignifughe	(EN ISO 9239-1) Euroclass Cfl s1* (EN 13501-1)						
Dimensional Stability / Dimensionsstabilität / Estabilidad Dimensional / Stabilité dimensionnelle / Dimensionele stabiliteit / Test Stabilità dimensionale	≤ 0.2% (EN 986)						
Impact Sound Insulation (ΔL_w) / Trittschallverbesserungsmaß / Impacto Aislamiento Acústico / Réduction du bruit d'impact / Contactgeluid absorptie / Isolamento all'impatto acustico	16 dB (EN ISO 10140-3)						
Rating of Sound Absorption / Gewichteter Schallabsorptionskoeffizient / Clasificación de Absorción de Sonido / Coefficient d'absorption acoustique / Waarde geluidsabsorptie / Valutazione dell'assorbimento acustico	α _w 0.15 (EN ISO 11654)						
Sound Absorption / Schallabsorptionsgrad / Absorción de Sonido / Absorption acoustique / Geluidsabsorptie / Assorbimento acustico	125Hz 0.01	250Hz 0.01	500Hz 0.06	1000Hz 0.14	2000Hz 0.25	4000Hz 0.33	(EN ISO 354) α _s
Style	4199		5m ² - 20 tiles per box (50 x 50 cm ± 0.2%)				

EN 14041




DOP: 1037/125246
textile floor covering
EN 1307




Quarter Turn


100%

Recycled Nylon







17ESCESA




GUST




NCS




0.36




2.0 kW




16dB




0.15



≥ 27



≥ 2.4



A+ A B C

www.interface.com

* Bfl s1 on request / Bfl s1 auf Anfrage / Bfl s1 Bajo pedido / Bfl s1 disponible en option. Tarif et conditions sur demande / Bfl s1 Op aanvraag