

DESCRIPTION			
Type of flooring	EN ISO 24011 (EN 548)	-	Linoleum
Pattern	-	-	Moiré
Total thickness	EN ISO 24346 (EN 428)	mm	4.0
Backing	-	-	Jute fabric
Weight	EN ISO 23997 (EN 430)	g/sqm	4700
Width of sheet	EN ISO 24341 (EN 426)	cm	200
Length of sheet	EN ISO 24341 (EN 426)	m	app.28
CLASSIFICATION			
Norm / Product specification	-	-	EN 14904 / DIN 18032-2
European classification	EN ISO 10874 (EN 685)	class	23 / 34 / 43
Fire rating	EN 13501-1	class	Cfl-s1*
Dynamic friction coefficient	EN 13893	-	0.4-0.6 μ - Fulfilled
Friction	EN 14904	-	80-110 Fulfilled
Impact sound insulation	EN ISO 10140	dB	6 dB
PERFORMANCES			
Residual indentation	EN ISO 24343-1 (EN 433)	mm	\leq 0.20
Colour fastness	EN ISO 105 - B02	degree	\geq 6
Light reflection	DIN 5036-3	-	p \geq 0.20 fulfilled (except colours 0024 and 0081)
Static electrical propensity	EN 1815	kV	app. 2.0
Castor chair test (Type W)	ISO 4918	-	OK
Thermal resistance	EN 12667	Sqm,K/W	0.023
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.17
Chemical products resistance	EN ISO 26987 (EN 423)	class	Resistance to fat and mineral oil and short term resistance against diluted acids
Antibacterial activity	JIS Z 2801	-	DLW linoleum has an antibacterial activity
CERTIFICATES AND LABELS			
     			
CE MARKING			
	EN 14904 : 2006	-	  
		-	 